

# Model OMS-EP60W-12V

File Number: E528990

## COMPANY

### E-POWER Co Ltd

903~907 SmartSquare, 1, Maehwasandan 3-gil  
Siheung-si, Gyeonggi-do 14931 Republic of Korea

## MODEL INFO

OMS-EP60W-12V  
Drivers

## SIGN ACCESSORIES

## VALUE

Application	LED Lighting
Component Type	Drivers
Circuit Type	Class 2
Enclosure Required?	may require an enclosure (to be determined in the end use)
Environmental Suitability	Wet, Damp or Dry Location
Max Ambient Temp	50 °C

## INPUT RATINGS

Input Voltage Minimum (v)	Input Voltage Maximum (v)	Input AC/DC	Input Frequency (Hz)	Input Power Minimum (w)	Input Power Maximum (w)	Input Current Minimum (A)	Input Current Maximum (A)
100	277	ac	50/60	66	66	1.06	1.06

## OUTPUT RATINGS

Output Voltage Minimum (v)	Output Voltage Maximum (v)	Output AC/DC	Output Frequency (Hz)	Output Power Minimum (w)	Output Power Maximum (w)	Output Current Minimum (A)	Output Current Maximum (A)	Constant Current/Voltage
12	12	dc	--	--	--	5	5	CV

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."

# Model OMP-EP100PFC-12V

File Number: E528990

## COMPANY

### E-POWER Co Ltd

903~907 SmartSquare, 1, Maehwasandan 3-gil  
Siheung-si, Gyeonggi-do 14931 Republic of Korea

## MODEL INFO

OMP-EP100PFC-12V  
Drivers

## SIGN ACCESSORIES

## VALUE

Application	LED Lighting
Component Type	Drivers
Circuit Type	Isolated
Enclosure Required?	may require an enclosure (to be determined in the end use)
Environmental Suitability	Wet, Damp or Dry Location

## INPUT RATINGS

Input Voltage Minimum (v)	Input Voltage Maximum (v)	Input AC/DC	Input Frequency (Hz)	Input Power Minimum (w)	Input Power Maximum (w)	Input Current Minimum (A)	Input Current Maximum (A)
120	277	ac	50/60	--	--	1.2	1.2

## OUTPUT RATINGS

Output Voltage Minimum (v)	Output Voltage Maximum (v)	Output AC/DC	Output Frequency (Hz)	Output Power Minimum (w)	Output Power Maximum (w)	Output Current Minimum (A)	Output Current Maximum (A)	Constant Current/Voltage
12	12	dc	--	100	100	8.3	8.3	--

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."

# Model OMP-EP150PFC-12V

File Number: E528990

## COMPANY

### E-POWER Co Ltd

903~907 SmartSquare, 1, Maehwasandan 3-gil  
Siheung-si, Gyeonggi-do 14931 Republic of Korea

## MODEL INFO

OMP-EP150PFC-12V  
Drivers

## SIGN ACCESSORIES

## VALUE

Application	LED Lighting
Component Type	Drivers
Circuit Type	Isolated
Enclosure Required?	may require an enclosure (to be determined in the end use)
Environmental Suitability	Wet, Damp or Dry Location

## INPUT RATINGS

Input Voltage Minimum (v)	Input Voltage Maximum (v)	Input AC/DC	Input Frequency (Hz)	Input Power Minimum (w)	Input Power Maximum (w)	Input Current Minimum (A)	Input Current Maximum (A)
120	277	ac	50/60	--	--	1.8	1.8

## OUTPUT RATINGS

Output Voltage Minimum (v)	Output Voltage Maximum (v)	Output AC/DC	Output Frequency (Hz)	Output Power Minimum (w)	Output Power Maximum (w)	Output Current Minimum (A)	Output Current Maximum (A)	Constant Current/Voltage
12	12	dc	--	150	150	12.5	12.5	--

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."

# Model OMP-EP200PFC-12V

File Number: E528990

## COMPANY

### E-POWER Co Ltd

903~907 SmartSquare, 1, Maehwasandan 3-gil  
Siheung-si, Gyeonggi-do 14931 Republic of Korea

## MODEL INFO

OMP-EP200PFC-12V  
Drivers

## SIGN ACCESSORIES

## VALUE

Application	LED Lighting
Component Type	Drivers
Circuit Type	Isolated
Enclosure Required?	may require an enclosure (to be determined in the end use)
Environmental Suitability	Wet, Damp or Dry Location

## INPUT RATINGS

Input Voltage Minimum (v)	Input Voltage Maximum (v)	Input AC/DC	Input Frequency (Hz)	Input Power Minimum (w)	Input Power Maximum (w)	Input Current Minimum (A)	Input Current Maximum (A)
120	277	ac	50/60	--	--	2.5	2.5

## OUTPUT RATINGS

Output Voltage Minimum (v)	Output Voltage Maximum (v)	Output AC/DC	Output Frequency (Hz)	Output Power Minimum (w)	Output Power Maximum (w)	Output Current Minimum (A)	Output Current Maximum (A)	Constant Current/Voltage
12	12	dc	--	200	200	16.6	16.6	--

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."

# Model OMP-EP300PFC-12V

File Number: E528990

## COMPANY

### E-POWER Co Ltd

903~907 SmartSquare, 1, Maehwasandan 3-gil  
Siheung-si, Gyeonggi-do 14931 Republic of Korea

## MODEL INFO

OMP-EP300PFC-12V  
Drivers

## SIGN ACCESSORIES

## VALUE

Application	LED Lighting
Component Type	Drivers
Circuit Type	Isolated
Enclosure Required?	may require an enclosure (to be determined in the end use)
Environmental Suitability	Wet, Damp or Dry Location

## INPUT RATINGS

Input Voltage Minimum (v)	Input Voltage Maximum (v)	Input AC/DC	Input Frequency (Hz)	Input Power Minimum (w)	Input Power Maximum (w)	Input Current Minimum (A)	Input Current Maximum (A)
120	277	ac	50/60	--	--	3.5	3.5

## OUTPUT RATINGS

Output Voltage Minimum (v)	Output Voltage Maximum (v)	Output AC/DC	Output Frequency (Hz)	Output Power Minimum (w)	Output Power Maximum (w)	Output Current Minimum (A)	Output Current Maximum (A)	Constant Current/Voltage
12	12	dc	--	60	60	25	25	--

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."

# Model OMS-EP60W-24V

File Number: E528990

## COMPANY

### E-POWER Co Ltd

903~907 SmartSquare, 1, Maehwasandan 3-gil  
Siheung-si, Gyeonggi-do 14931 Republic of Korea

## MODEL INFO

OMS-EP60W-24V  
Drivers

## SIGN ACCESSORIES

## VALUE

Application	LED Lighting
Component Type	Drivers
Circuit Type	Class 2
Enclosure Required?	may require an enclosure (to be determined in the end use)
Environmental Suitability	Wet, Damp or Dry Location
Max Case Temp	71.2 °C

## STANDARD CONDITIONS OF USE

1. Rated output loading for LED drivers was achieved using electronic loads. The temperature tests were performed at nominal 40 °C ambient.
2. Temperature tests were performed according to Supplement SG. During temperature testing of the end product, evaluation of this component can be limited to the temperature at the Test Measurement Point Tc. The absolute value at this point cannot exceed 71.2 °C. See III. 1 for the location of the Tc point.
3. These products utilize a Class A (105) electrical insulation system.
4. These products are provided with 18 AWG, stranded, leads, rated 105 °C, 300 V minimum for input connections. And provided with 16 AWG, 300 V, 105 °C for output connections.
5. These products have been evaluated for use with a source of supply noted in the product characteristics table (input type) and electrical ratings noted in the electrical ratings table. Suitability of these products with other sources of supply or electrical ratings is to be determined in the end product.

6. These products are marked suitable for damp locations.

7. The LED Power Supply is intended for built-in factory assembled sign use, where the suitability of the enclosure, mounting, and input/output connections shall be considered in the end product.

8. LED driver or power supply spacing to thermoplastic, wood, fiber, or other combustible type enclosure materials shall be 1 in. unless temperature tested.

9. Two or more adjacent LED drivers or LED power supplies shall not be mounted closer than 1 in. end to end or 4 in. side to side unless temperature tested for the application

### INPUT RATINGS

Input Voltage Minimum (v)	Input Voltage Maximum (v)	Input AC/DC	Input Frequency (Hz)	Input Power Minimum (w)	Input Power Maximum (w)	Input Current Minimum (A)	Input Current Maximum (A)
120	277	ac	50/60	--	68	--	1.06

### OUTPUT RATINGS

Output Voltage Minimum (v)	Output Voltage Maximum (v)	Output AC/DC	Output Frequency (Hz)	Output Power Minimum (w)	Output Power Maximum (w)	Output Current Minimum (A)	Output Current Maximum (A)	Constant Current/Voltage
24	24	dc	--	--	68	--	2.5	CV

Report Date: 2024-04-23  
Revision Date: 2026-01-29

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."

# Model OMS-EP96W-24V

File Number: E528990

## COMPANY

### E-POWER Co Ltd

903~907 SmartSquare, 1, Maehwasandan 3-gil  
Siheung-si, Gyeonggi-do 14931 Republic of Korea

## MODEL INFO

OMS-EP96W-24V  
Drivers

## SIGN ACCESSORIES

## VALUE

Application	LED Lighting
Component Type	Drivers
Circuit Type	Class 2
Enclosure Required?	may require an enclosure (to be determined in the end use)
Environmental Suitability	Wet, Damp or Dry Location
Max Case Temp	62.8 °C

## STANDARD CONDITIONS OF USE

1. Rated output loading for LED drivers was achieved using electronic loads. The temperature tests were performed at nominal 40 °C ambient.
2. Temperature tests were performed according to Supplement SG. During temperature testing of the end product, evaluation of this component can be limited to the temperature at the Test Measurement Point Tc. The absolute value at this point cannot exceed 62.8 °C. See III. 1 for the location of the Tc point.
3. These products utilize a Class A (105) electrical insulation system.
4. These products are provided with 18 AWG, stranded, leads, rated 105 °C, 300 V minimum for input connections. And provided with 16 AWG, 300 V, 105 °C for output connections.
5. These products have been evaluated for use with a source of supply noted in the product characteristics table (input type) and electrical ratings noted in the electrical ratings table. Suitability of these products with other sources of supply or electrical ratings is to be determined in the end product.

6. These products are marked suitable for damp locations.
7. The LED Power Supply is intended for built-in factory assembled sign use, where the suitability of the enclosure, mounting, and input/output connections shall be considered in the end product.
8. LED driver or power supply spacing to thermoplastic, wood, fiber, or other combustible type enclosure materials shall be 1 in. unless temperature tested.
9. Two or more adjacent LED drivers or LED power supplies shall not be mounted closer than 1 in. end to end or 4 in. side to side unless temperature tested for the application

#### INPUT RATINGS

Input Voltage Minimum (v)	Input Voltage Maximum (v)	Input AC/DC	Input Frequency (Hz)	Input Power Minimum (w)	Input Power Maximum (w)	Input Current Minimum (A)	Input Current Maximum (A)
120	277	ac	50/60	--	110	--	1.44

#### OUTPUT RATINGS

Output Voltage Minimum (v)	Output Voltage Maximum (v)	Output AC/DC	Output Frequency (Hz)	Output Power Minimum (w)	Output Power Maximum (w)	Output Current Minimum (A)	Output Current Maximum (A)	Constant Current/Voltage
24	24	dc	--	--	96	--	4	CV

Report Date: 2024-04-23  
Revision Date: 2026-01-29

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."

# Model OMP-EP192W-24V

File Number: E528990

## COMPANY

### E-POWER Co Ltd

903~907 SmartSquare, 1, Maehwasandan 3-gil  
Siheung-si, Gyeonggi-do 14931 Republic of Korea

## MODEL INFO

OMP-EP192W-24V  
Drivers

SIGN ACCESSORIES	VALUE
Application	LED Lighting
Component Type	Drivers
Circuit Type	Class 2
Enclosure Required?	may require an enclosure (to be determined in the end use)
Environmental Suitability	Damp or Dry Location Only
Max Case Temp	90 °C
<b>STANDARD CONDITIONS OF USE</b>	

Rated output loading for LED driver(s) was achieved using electronic loads. The temperature tests were performed at nominal 45 °C ambient.

Temperature tests were performed according to Supplement SG. During temperature testing of the end product, evaluation of this component can be limited to the temperature at the Test Measurement Point Tc. The absolute value at this point cannot exceed 90.0 °C. See III. 1 for the location of the Tc point.

This product utilize a UL Recognized OBJY2 Class 130 (B) electrical insulation system.

This product is provided with 18 AWG, stranded, leads, rated 105 °C, 300 V minimum for input connections. And provided with 16 AWG, 300 V, 105 °C for output connections.

This product has been evaluated for use with a source of supply noted in the product characteristics table (input type) and electrical ratings noted in the electrical ratings table. Suitability of these products with other sources of supply or electrical ratings is to be determined in the end product.

This product is marked suitable for damp locations.

The LED Power Supply is intended for built-in factory assembled sign use, where the suitability of the enclosure, mounting, and input/output connections shall be considered in the end product.

This product has multiple outputs. Interconnection of these outputs has not been evaluated. Acceptability of interconnection of these outputs (and the associated circuits) is to be considered as part of the end product evaluation.

LED driver or power supply spacing to thermoplastic, wood, fiber, or other combustible type enclosure materials shall be 1 in. unless temperature tested.

Two or more adjacent LED drivers or LED power supplies shall not be mounted closer than 1 in. end to end or 4 in. side to side unless temperature tested for the application.

**INPUT RATINGS**

<b>Input Voltage Minimum (V)</b>	<b>Input Voltage Maximum (V)</b>	<b>Input AC/DC</b>	<b>Input Frequency (Hz)</b>	<b>Input Power Minimum (W)</b>	<b>Input Power Maximum (W)</b>	<b>Input Current Minimum (A)</b>	<b>Input Current Maximum (A)</b>
120	277	ac	50/60	210	--	2	--

OUTPUT RATINGS								
Output Voltage Minimum (V)	Output Voltage Maximum (V)	Output AC/DC	Output Frequency (Hz)	Output Power Minimum (W)	Output Power Maximum (W)	Output Current Minimum (A)	Output Current Maximum (A)	Constant Current/Voltage
24	--	dc	--	96	--	4	--	CV
24	--	dc	--	96	--	4	--	CV

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."

## Model OMP-EP288W-24V

File Number: E528990

### COMPANY

#### E-POWER Co Ltd

903~907 SmartSquare, 1, Maehwasandan 3-gil  
Siheung-si, Gyeonggi-do 14931 Republic of Korea

### MODEL INFO

OMP-EP288W-24V  
Drivers

SIGN ACCESSORIES		VALUE
Application		LED Lighting
Component Type		Drivers
Circuit Type		Class 2
Enclosure Required?	may require an enclosure (to be determined in the end use)	
Environmental Suitability	Damp or Dry Location Only	
<b>STANDARD CONDITIONS OF USE</b>		

1. Rated output loading for LED drivers was achieved using electronic loads. The temperature tests were performed at nominal 45 °C ambient.
2. Temperature tests were performed according to Supplement SG. During temperature testing of the end product, evaluation of this component can be limited to the temperature at the Test Measurement Point Tc. The absolute value at this point cannot exceed 80.3 °C. See Ill. 1 for the location of the Tc point.
3. These products utilize a UL Recognized OBJY2 Class 130 (B) electrical insulation system.
4. These products are provided with 18 AWG, stranded, leads, rated 105 °C, 300 V minimum for input connections. And provided with 16 AWG, 300 V, 105 °C for output connections.
5. These products have been evaluated for use with a source of supply noted in the product characteristics table (input type) and electrical ratings noted in the electrical ratings table. Suitability of these products with other sources of supply or electrical ratings is to be determined in the end product.
6. These products are marked suitable for damp locations.
7. The LED Power Supply is intended for built-in factory assembled sign use, where the suitability of the enclosure, mounting, and input/output connections shall be considered in the end product.
8. This product has multiple outputs. Interconnection of these outputs has not been evaluated. Acceptability of interconnection of these outputs (and the associated circuits) is to be considered as part of the end product evaluation.
9. LED driver or power supply spacing to thermoplastic, wood, fiber, or other combustible type enclosure materials shall be 1 in. unless temperature tested.
10. Two or more adjacent LED drivers or LED power supplies shall not be mounted closer than 1 in. end to end or 4 in. side to side unless temperature tested for the application.

**INPUT RATINGS**

<b>Input Voltage Minimum (V)</b>	<b>Input Voltage Maximum (V)</b>	<b>Input AC/DC</b>	<b>Input Frequency (Hz)</b>	<b>Input Power Minimum (W)</b>	<b>Input Power Maximum (W)</b>	<b>Input Current Minimum (A)</b>	<b>Input Current Maximum (A)</b>
120	277	ac	50/60	310	--	2.6	--

**OUTPUT RATINGS**

<b>Output Voltage Minimum (V)</b>	<b>Output Voltage Maximum (V)</b>	<b>Output AC/DC</b>	<b>Output Frequency (Hz)</b>	<b>Output Power Minimum (W)</b>	<b>Output Power Maximum (W)</b>	<b>Output Current Minimum (A)</b>	<b>Output Current Maximum (A)</b>	<b>Constant Current/Voltage</b>
24	--	dc	--	96	--	4	--	CV
24	--	dc	--	96	--	4	--	CV
24	--	dc	--	96	--	4	--	CV

Product ID: 8016001

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <https://www.ul.com/about/locations>.

## Sign Accessories - Component

### COMPANY

#### E-POWER Co Ltd

903~907 SmartSquare, 1, Maehwasandan 3-gil  
Siheung-si, Gyeonggi-do 14931 Republic of Korea

E528990

Marking: Company name and model designation.

Note: For additional marking information, refer to the [Guide Information Page](#).

*View model for additional information*

**Drivers**, Model(s): [IPS-EP100W-24V](#), [IPS-EP60W-12V](#), [IPS-EP60W-24V](#), [OMP-EP100PFC-12V](#), [OMP-EP150PFC-12V](#), [OMP-EP192W-24V](#), [OMP-EP200PFC-12V](#), [OMP-EP288W-24V](#), [OMP-EP300PFC-12V](#), [OMP-EP60PFC-12V](#), [OMS-EP60W-12V](#), [OMS-EP96W-24V](#)

Last Updated on 2024-09-04

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."

# Model IPS-EP60W-24V

File Number: E528990

## COMPANY

### E-POWER Co Ltd

903~907 SmartSquare, 1, Maehwasandan 3-gil  
Siheung-si, Gyeonggi-do 14931 Republic of Korea

## MODEL INFO

IPS-EP60W-24V

Drivers

SIGN ACCESSORIES	VALUE
Application	LED Lighting
Component Type	Drivers
Circuit Type	Class 2
Enclosure Required?	may require an enclosure (to be determined in the end use)
Environmental Suitability	Damp or Dry Location Only
Max Case Temp	87.5 °C
Max Ambient Temp	50 °C

INPUT RATINGS							
Input Voltage Minimum (V)	Input Voltage Maximum (V)	Input AC/DC	Input Frequency (Hz)	Input Power Minimum (W)	Input Power Maximum (W)	Input Current Minimum (A)	Input Current Maximum (A)
100	277	ac	50/60	68	68	1.073	1.073

OUTPUT RATINGS								
Output Voltage Minimum (V)	Output Voltage Maximum (V)	Output AC/DC	Output Frequency (Hz)	Output Power Minimum (W)	Output Power Maximum (W)	Output Current Minimum (A)	Output Current Maximum (A)	Constant Current/Voltage
24	24	dc	--	--	--	2.5	2.5	CV

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."